

# STANDARD MACHINES PRODUCT LINE



Features	P650	P702	415-G1	SO425
Performance Rating	Entry level Semi Auto Tabletop ★ ★ ★	General Purpose ★ ★ ★ ★	Premium ★ ★ ★ ★ ★	Optimum ★ ★ ★ ★ ★
Everyday Use	Yes	Yes	Yes	Yes
Machine Life (Cycles)	>1 Million	2 Million	3 Million +	5 Million +
PLC Controls for Automation	No	Optional	Standard	Standard
Conveyors Belt tops	No	Optional	Optional	Optional
Power Roller Tops	No	Optional	Optional	Optional
Fully Automatic	No	Optional	Optional	Optional
Most Demanding 24/7 Applications	No	No	Yes	Yes
Side Seal	No	Optional	Optional	No
DC Drive	Yes	Yes	Yes	Yes
System Design	Electronic	Electronic	Mechanical & Electronic	Electronic
Usable in Harsh Environments	No	Optional	Optional	Optional
Seal Engine	Standard Duty	Standard Duty	Extra Heavy Duty	Heavy Duty
Tension	Up to 88 lbs.	Up to 120 lbs.	Up to 180 lbs.	Up to 120 lbs.
Operator Controls	Manual	Push Button	Push Button	Touch Screen
Strap Options	5, 6, 9, 12mm up to .028	5, 6, 9, 12mm up to .027	6, 9, 12mm up to .030	5, 6, 9, 12mm up to .028
Break Strength Range	250 to 600 lbs	120 to 450 lbs	250 to 600 lbs	120 to 500 lbs.
Cycles/min.	N/A	60	50	50
Special Feature	Premium seal and tension unit, adjustable temperature and cooling time.	Custom configurable	Highly customizable, high tension force capable, rugged for extreme environments	Strap width can be field convertible with no parts changes, wear parts minimized, tool-less clearing
Starting Price	\$	\$\$	\$\$\$	\$\$\$\$

© SM Comparison -131049 - August 2019

packaging@samuel.com  
www.samuelpsg.com  
**YOUR SUCCESS IS OUR BUSINESS**

U.S.A: 800-323-4424  
Canada: 800-607-8727

