

HEAD THIN OUT

ASME F&D 6% or 10%												
Head Thickness	10ga	7ga	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"		
Head Dia												
14-34"	0.025"											
36-59"	0.025"											
60-82"	0.035"					0.06"						
84-180"	0.035"					0.06"				0.07"		
2:1 ELLIPTICAL												
Head Thickness	10ga	7ga	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"		
Head Dia												
18-22"			0.035"									
24-34"			0.035"									
36-58"			0.045"				0.045"					
60-82"			0.045"				0.06"		0.065"			
84-94"			0.05"				0.06"		0.065"		0.070"	0.090"
96-118"			0.06"				0.06"		0.065"		0.080"	0.100"
120-144"					0.04"		0.063"			0.07"	0.105"	0.135"
120-144"					0.04"		0.063"			0.07"	0.105"	0.135"
ASME F&D 6% or 10%												
Head Thickness	10ga	7ga	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"		
Head Dia												
18-22"			0.050"									
24-34"												
36-58"												
60-82"					0.063"							
84-168"					0.063"					0.085"		0.150"

For other head types please contact:
LZR FIT Customer Care | 715.453.5326 | info@lzrfit.com

Phone: 715.453.5326
Fax: 715.453.6531
Email: info@lzrfit.com
Website: www.lzrfit.com