

# MODEL P702

## Automatic Strapping Machine

### FEATURES

- Up to 65 straps per minute
- 5 mm, 6 mm, 9 mm and 12 mm Polypropylene Strapping
- High performance DC brushless motor technology
- Precision electronic tension up to 100 lbs.
- Loop ejector
- Coil end strap ejector
- Anti jam technology
- Compact frame with internal strapping dispenser
- Auto strap loading at waist height
- Foot bar, foot pedal, photo eye and panel switch are standard on base models
- Track design insures precision strap placement
- Roller table tops standard on 33" wide sizes and up



# MODEL P702

## Automatic Strapping Machine

### STANDARD FEATURES

The P702 is a high speed automatic strapping machine. It features several creative designs that make it the most operator friendly machine in its class.

The operator control panel is hinged to allow access from either side of the machine. The Smart LCD display offers enhanced diagnostics and the ability to make adjustments.

The P702 features an inside mount strap dispenser that hinges up for strap loading at waist height or an outside mount dispenser for strap loading at waist height on the 12mm P702. The new quick release dispenser flange lock knob makes coil changes faster.

All P702 series machines have a hinged open top plate for easy access to the strapping head. They also feature quick release feed guides for immediate access to the strap feed system with the need for tools.

### AVAILABLE OPTIONS

- High Tension for 9 mm Model
- Low Height Configuration
- Extended Height Configuration
- Rear Foot Bar
- Automation Package
- Light Tree



Photo Eye



Hinged Open Tops



Adjustable Height

### SPECIFICATIONS

|                          |                               |                   |
|--------------------------|-------------------------------|-------------------|
| <b>Width*</b>            | 940 mm                        | 37"               |
| <b>Height*</b>           | 1422 mm                       | 56"               |
| <b>Depth*</b>            | 660 mm                        | 26"               |
| <b>Shipping Weight</b>   | 204 kg                        | 450 lbs           |
| <b>Table Height</b>      | 819 - 921 mm                  | 32 1/4" - 36 1/4" |
| <b>Minimum Pkg. Size</b> | W 70 x H 25 mm                | W 2 3/4" x H 1"   |
| <b>Maximum Pkg. Size</b> | Arch Width x Arch Height      |                   |
| <b>Strapping Speed</b>   | Up to 65 cycles per minute    |                   |
| <b>Strapping Used</b>    | 5, 6, 9, 12 mm                | 1/4", 3/8", 1/2"  |
|                          | Embossed or Smooth Strapping  |                   |
| <b>Tensioning Range</b>  | 1 - 45 kg                     | 2 - 100 lbs       |
| <b>Power Supply</b>      | 110 V (220, 230) Single Phase |                   |

\*Dimensions for 21" x 15" Arch size.

© 130988 - P702 - August 2019

Specifications are for guidance purposes only and subject to change without notice.



### P702B FULLY AUTOMATIC WITH CONVEYORS

#### FEATURES

- Up to 40 Packages per Minute in Single Strap Mode
- Cycle Speed Up To 65 Straps per Minute Operates with 5mm, 6mm, 9mm or 12mm Polypropylene Strapping
- Single, Double, Multiple Strap and Bypass Fully Automatic Operation with Photo Eyes
- Variable Conveyor Speed
- Maximum Package weight 75 lbs.



### P702Y SIDE SEAL

#### FEATURES

- Available with Integrated Roller Table, adjustable from 17.5" to 25.5"
- High Speed up to 65 Cycles per Minute
- Inside Mount Coil Dispenser
- 110 Volt single Phase Electrical
- Electronic Tension, 2-120 Pounds
- Lower Horizontal Track Clearance of 10.25" to 14.25" with Adjustable Leveling Pads
- Locking Casters
- Pushbutton Cycle Actuator on Panel

packaging@samuel.com  
www.samuelpsg.com

U.S.A: 800-323-4424  
Canada: 800-607-8727

  
**SAMUEL**  
PACKAGING SYSTEMS GROUP